
195 to 325 cm

LOAD CAPACITY: UP TO 1800 KG









Wheel for assisted deployment



Self-positioning adjustable feet




Mobile contact flap to connect to the floor of the van











DEPLOYMENT AND CLOSING

The ME ramp is popular for customers needing to load heavy equipment. Deployment of the ramp is simple and quick, thanks to its spring-assisted, fixed vertical, two-section opening. A double-spring version can be supplied on request for larger versions.

OPTIONAL EXTRAS



LEFT HAND SIDE WHEEL KIT

Designed to facilitate ramp deployment, closing and handling. Right hand as standard, or available on left-hand side as an option.

SUPPLEMENTARY 3RD PIECE KIT

Reduces the ramp angle and results in three folding ramp sec-

tions. Ideal for use with small ve-

hicles. Available with capacities

up to 1,000 kg, max. width of 100

cm and fixed length of 80 cm.



FOLDING SAFETY EDGES

Aluminium safety edges to enhance safety in certain operating conditions.



REMOVABLE EXTENSION KIT

Third removable piece equipped with wheels, to be added to the ramp when necessary. Available for capacities up to 1500 kg, with maximum width of 100 cm.

APPLICATION SECTORS



GARDENING LAWN **TRACTORS**



BUILDING QUAD BIKES CONSTRUCTION



CLEANING **MACHINES**



PALLET **TRUCKS**

PALLETS

| EXAMPLE MODELS | A (mm) | L (mm) | L2 (mm) | H (mm) | P (mm) | P1 (mm) | P2 (mm) | Capac. (Kg) | Weight* (Kg) |
|-------------------|-----------|-----------|------------|-----------|-----------|------------|------------|----------------|-----------------|
| ME 90 | 2200 | 1165 | 900 | 1215 | 95 | 250 | 8 | 600 | 79 |
| ME 95 | 2500 | 1215 | 950 | 1365 | 95 | 250 | 8 | 600 | 86 |
| ME 100 | 3000 | 1265 | 1000 | 1615 | 95 | 250 | 8 | 1000 | 104 |
| ME 100 | 3250 | 1265 | 1000 | 1740 | 95 | 250 | 8 | 1500 | 122 |
| ME 105 | 2700 | 1315 | 1050 | 1515 | 95 | 250 | 8 | 600 | 94 |
| ME 110 | 3000 | 1365 | 1100 | 1615 | 95 | 250 | 8 | 1500 | 129 |
| ME 110 | 2500 | 1365 | 1100 | 1365 | 95 | 250 | 8 | 1000 | 104 |
| ME 120 | 2700 | 1465 | 1200 | 1465 | 95 | 250 | 8 | 1000 | 115 |
| ME 120 | 3250 | 1465 | 1200 | 1740 | 95 | 250 | 8 | 1500 | 146 |
| ME 125 | 2800 | 1515 | 1250 | 1515 | 95 | 250 | 8 | 1000 | 126 |
| ME 125 | 3000 | 1515 | 1250 | 1615 | 95 | 250 | 8 | 1500 | 143 |
| ME 130 | 3000 | 1565 | 1300 | 1615 | 95 | 250 | 8 | 1000 | 137 |
| ME 130 | 3250 | 1565 | 1300 | 1740 | 95 | 250 | 8 | 1500 | 157 |
| ME 135 | 3200 | 1615 | 1350 | 1715 | 95 | 250 | 8 | 1500 | 158 |
| ME 135 | 3250 | 1615 | 1350 | 1740 | 95 | 250 | 8 | 1800 | 169 |

^{*} The specified weight does not include the installation kit, which depends on the van. (min. 2 kg - max. 7 kg)

