

REMOVABLE, LIGHT-WEIGHT AND PRACTI-CAL LOADING RAMP WITH ANODISED AL-UMINIUM ANTI-SLIP PLATFORM.



STANDARD DIMENSIONS

DIMENSIONS
Width 85 cm
Length 200, 225 and 250 cm



COLOUR White









Safety edges (6 cm)



Gas strut for easy handling



Quick release and coupling.











DEPLOYMENT: The WM Superlight is extremely lightweight, using both spring and gas strut assistance. An external swivel kit is supplied on request, making it possible to gain access to the van like a second door.

REMOVABILITY AND TRANSPORT: Quick release handles allow for easy removal of the ramp, leaving the load area unobstructed. The keyhole locating plates allow for easy and quick transfer between vehicles.

OPTIONAL EXTRAS

FIXED INSTALLATION



A fixed base can be mounted to the ramp on request. This means the ramp becomes fixed and can no longer be removed from the van. This solution simplifies and streamlines installation operations.



EXTERNAL SWIVELLING

Swivel kit that makes it possible to rotate the ramp through 90° toward the exterior of the van. This system makes it possible to gain access to the van's cargo area without using the ramp (e.g. for loading pallets with a forklift truck).


APPLICATION SECTORS





MEDICAL **AMBULANCES**



DISABLED USERS PASSENGER **TRANSPORT**







ALL MODELS	A (mm)	L (mm)	L2 (mm)	H (mm)	P (mm)	P1 (mm)	P2 (mm)	Capac. (kg)	Weight* (kg)
SUPERLIGHT	2000	1100	850	1085	215	345	60	250	40
SUPERLIGHT	2250	1100	850	1210	215	345	60	250	45
SUPERLIGHT	2500	1100	850	1335	215	345	60	250	50

^{*} The specified weight does not include the installation kit, 5 kg. The external swivelling optional weighs +6 kg